



# ELF HTX 3825

## 0W-20

*100% synthetic lubricant for competition engines*



*"F1 and Motorcycle GP drivers consider ELF HTX 38xx to be one of the best ultra fluid competition lubricants in the world."*

### Uses

- **ELF HTX 3825** is a multigrade lubricant designed for 4-stroke petrol engines.
- **ELF HTX 3825** is specially designed to obtain maximum engine power over short and/or very short runs.
- **ELF HTX 3825** is especially recommended for short, intense races where maximum performance is sought such as sprint circuit and qualifying races.
- Directly based on ELF experience in Formula 1 and Motorcycle GP, the **ELF HTX 38xx** range is particularly used for developing and running engines in Motorcycle GP, Superbike and Formula 3.
- **ELF HTX 3825** is used for the following applications:
  - 4-stroke naturally-aspirated and turbocharged petrol engines, up to 19,000 rpm and more
- **ELF HTX 3825** is perfectly suited to competitions of very short duration:
  - Qualifying races
  - Hill climb races

### Characteristics

	Typical values	Units	Methods
Density at 15°C	0.845	g/ml	ASTM D-1298
Viscosity at 40°C	39.57	mm <sup>2</sup> /s	ASTM D-445
Viscosity at 100°C	7.63	mm <sup>2</sup> /s	ASTM D-445
Viscosity HTHS	2.42	mPa.s	ASTM D-4741
Flash point	> 220	°C	ASTM D-92

## 100% synthetic lubricant for competition engines

### ELF HTX 38xx

ELF HTX 3825 is miscible in any proportion with ELF HTX 3818 (5W-30), ELF HTX 3821 (5W-30), ELF HTX 805 (5W-50), ELF HTX 825 (10W-60) and ELF HTX 835 (15W-40).

ELF HTX 3818, ELF HTX 3821 and ELF HTX 3825 are primarily performance-g geared lubricants.

In the ELF HTX 38xx range, ELF HTX 3825 is the ultimate lubricant in terms of performance.

For greater protection (longer use), we recommend the ELF HTX 8xx range.

### Properties

CHARACTERISTICS	→	TECHNICAL GAINS	→	ENGINE BENEFITS
Particularly low <b>viscosity</b> (0W-20)	→	Very great reduction in <b>frictional loss</b>	→	Maximum power over entire speed range
Reversible <b>high shear viscosity</b> (HTHS)	→	Sharp reduction in <b>energy wasted</b> through viscous friction	→	Spontaneous power gain at high and very high speeds
Addition of specific <b>frictional modifiers</b>	→	Molecular <b>adsorption</b> on moving mechanical parts Excellent <b>lubrication</b> at high and very high speeds	→	Maintains engine lubrication conditions to give maximum performance at high and very high speeds

### Recommendations

- ELF HTX 3825 works perfectly up to 19,000 rpm.
- Due to its ultra fluid grade, ELF HTX 3825 is designed for very short runs such as qualifying races.

## *100% synthetic lubricant for competition engines*

- Due to its ultra fluid grade, it is recommended to carefully monitor mileage between each **ELF HTX 3825** oil change.
- Compatibility with the materials of the lubrication circuit:
  - No known incompatibility to date
  - Compatible in particular with silicon, fluorine, acrylic and nitrile type joints
- There is no specific precaution to take on first use of **ELF HTX 3825** other than removing the previous lubricant and replacing the oil filter.
- The use of an external additive (like engine remetalling) is not recommended.

### Storage

To preserve its original properties, **ELF HTX 3825** must be handled and stored away from extreme weather conditions. The can must be carefully closed again after each use.

### Glossary

#### **100% SYNTHETIC:**

Unlike certain lubricants on the market bearing the synthetic label, **ELF HTX 3825** really contains no mineral base.

#### **SHEAR:**

Distortion of lubricant when subjected to high speeds and loads.

#### **VISCOSITY HTHS** (High Temperature/High Shear):

Viscosity measured at High Temperature (150°C) and High Shear ( $10^6 \text{ s}^{-1}$ ).